

WHAT IS CLAIMED IS:

1. A privacy enclosure, comprising:
 - a) a rigid enclosure structure having a stowed configuration and an expanded configuration, the rigid enclosure structure being configured to:
 - i) lift from the stowed configuration to provide expansion in a first vertical direction; and
 - ii) extend laterally to provide expansion in a second lateral direction;
 - b) wherein the expanded configuration of the rigid enclosure structure being defined by expansion of the rigid enclosure structure in the first vertical direction and the second lateral direction.
2. The privacy enclosure of claim 1, wherein the rigid enclosure structure includes a pivoting wall structure having a first end and a second end, the first end being configured to pivot upward relative to the second end to provide expansion in the first vertical direction.
3. The privacy enclosure of claim 2, wherein the rigid enclosure structure includes a sidewall construction joined to the pivoting wall structure, the sidewall construction being configured to extend laterally outward from the pivoting wall structure.
4. The privacy enclosure of claim 3, wherein the sidewall construction includes a first sidewall construction fixed to the pivoting wall structure and a second moveable sidewall construction, the second moveable sidewall construction being configured to move relative to the first sidewall construction.
5. The privacy enclosure of claim 1, wherein the rigid enclosure structure includes an upper region and a lower region, the upper region of the rigid enclosure structure being configured to stow within the lower region.
6. The privacy enclosure of claim 5, further including a base that defines the lower region of the rigid enclosure structure, the upper region of the rigid enclosure structure

being sized to fit within the base when the rigid enclosure structure is in the stowed configuration.

7. The privacy enclosure of claim 6, wherein upper region of the rigid enclosure structure includes a pivoting wall, the pivoting wall and the base defining a bench for seating when the rigid enclosure structure is in the stowed configuration.

8. The privacy enclosure of claim 5, wherein the upper region includes a first door section and the lower region includes a second door section, the first and second door sections being configured to interlock with one another when the rigid enclosure structure is in the expanded configuration.

9. The privacy enclosure of claim 5, wherein the upper region includes a necked portion and the lower region includes an opening, the necked portion of the upper region being configured to fit within the opening of the lower region when the rigid enclosure structure is raised from the stowed configuration to provide expansion in the first vertical direction.

10. The privacy enclosure of claim 1, wherein the rigid enclosure structure includes a first wall section and a second wall section, at least one of the first and second wall sections being configured to slide relative to the other to provide expansion in the second lateral direction.

11. The privacy enclosure of claim 10, wherein the first and second wall sections include a tongue and groove arrangement to provide expansion in the second lateral direction.

12. A privacy enclosure, comprising:

- a) a plurality of rigid walls defining an interior, the interior being sized for use as a changing room, the rigid walls including at least a first rigid wall and a second rigid wall, wherein:

- i) the first rigid wall is configured to pivot upward from a first position to a generally vertical position; and
- ii) the second rigid wall is configured to laterally extend in a direction outward from the first rigid wall when the first rigid wall is in the vertical position.

13. The enclosure of claim 12, wherein the first rigid wall includes a seating area configured to seat users when the first rigid wall is positioned in the first position.

14. The enclosure of claim 12, wherein the second rigid wall includes a first section fixed relative to the first rigid wall, and a second section slideable relative to the first section, the second section being configured to slide in the direction outward from the first rigid wall when the first rigid wall is in the vertical position.

15. The enclosure of claim 14, wherein the first and second sections of the second rigid wall are nested when the first rigid wall is positioned in the first position.

16. A privacy enclosure arrangement, comprising:

- a) a lower base;
- b) a stowable enclosure coupled to the lower base, the stowable enclosure including:
 - i) a rigid outer wall structure configured to expand from a stowed configuration to an expanded configuration;
- c) wherein at least a portion of the lower base and the rigid outer wall structure define an interior when the rigid outer wall structure is in the expanded configuration;
- d) a storage compartment located adjacent to the interior of the privacy enclosure arrangement; and
- e) a toilet moveable between the storage compartment and the interior of the privacy enclosure arrangement.

17. The arrangement of claim 16, wherein the toilet is arranged to selectively slide out from the storage compartment when the rigid outer wall structure is in the expanded configuration.

18. The arrangement of claim 16, wherein the storage compartment is defined by the lower base.

19. The arrangement of claim 16, wherein the rigid outer wall structure expands from the stowed configuration to the expanded configuration in a first direction and then a second direction perpendicular to the first direction.

20. A boat having a privacy enclosure, the privacy enclosure comprising:

- a) an enclosure structure having a rigid exterior, the rigid exterior including:
 - i) a plurality of wall structures; and
 - ii) a door hinged to one of the plurality of wall structures;
- b) the enclosure structure being selectively positionable in:
 - i) a collapsed configuration that permits the enclosure to be stowed; and
 - ii) an expanded configuration wherein an average-sized adult can stand within the interior volume of the enclosure;
- c) the enclosure structure defining a toilet region and a changing room region when selectively positioned in the expanded configuration, the changing room region being adjacent to the toilet region.

21. The boat of claim 20, further including a toilet moveable between the toilet region and a storage region.

22. The boat of claim 21, wherein the changing room region enlarges when the toilet is moved into the storage region.

23. The boat of claim 20, wherein the changing room region extends a length beyond the toilet region, the length being in the range of about 24 inches and 36 inches.
24. The boat of claim 20, wherein the changing room region extends at least _____ inches beyond the toilet region.
25. The boat of claim 20, wherein the enclosure structure is positionable in:
- a) a first position having a first height;
 - b) a second position having an initial length and a second height, the second height being greater than the first height; and
 - c) a third position having an extended length, the extended length being greater than the initial length.
26. The boat of claim 20, wherein the enclosure structure includes a base, the plurality of wall structure being selectively positioning within the base.
27. The boat of claim 26, wherein the base includes a compartment sized and configured to stow a toilet.
28. The boat of claim 20, wherein the enclosure structure is secure to secured to a deck of the boat.
29. A method of expanding a privacy enclosure, the method comprising:
- a) providing an enclosure structure;
 - b) raising the enclosure structure from a reduced height configuration to a raised height configuration, the raised height configuration permitting an average-sized adult to stand within the enclosure structure; and
 - c) laterally expanding the enclosure structure from a first length to a second increased length.

30. The method of claim 29, wherein the step of raising the enclosure structure includes pivoting a first wall of the closure structure to a generally vertical orientation.
31. The method of claim 29, wherein the step of expanding the enclosure structure includes pulling a second wall laterally outward from the first wall.
32. An privacy enclosure, comprising:
- a) a rigid wall construction selectively positionable in a stowed configuration and an expanded configuration;
 - b) a main interior defined by the rigid wall construction;
 - c) a toilet storage region located adjacent to the main interior; and
 - d) a toilet movable between the main interior and the toilet storage region.